



CONTINUOUS BEAD OF JM SINGLE PLY LVOC CAULK

JM SINGLE PLY SEALING MASTIC BEHIND GUTTER FLANGE

JM DRAIN BAR FDB-40
1/4" (8mm) GAP BETWEEN SECTIONS-FASTENED 6" O.C. WITH APPROPRIATE FASTENERS

EXTEND FIELD SHEET 1/2" (13 mm) BELOW DRAIN BAR

GUTTER AND BRACKETS BY OTHERS
RE: SMACNA OR NRCA

JM EPDM MEMBRANE ADHERED, BALLASTED OR MECHANICALLY FASTENED

JM EPDM MEMBRANE ADHESIVE (FOR ADHERED SPECIFICATIONS ONLY)

JM INSULATION / COVER BOARD

WOOD NAILER SECURELY ANCHORED TO DECK-RE: DETAIL E-FE-M1

APPROVED DECK

NOTES:

1. REFER TO JOHNS MANVILLE WEBSITE (www.jm.com) FOR MOST UP-TO-DATE INFORMATION.
2. PLEASE SEE SINGLE PLY FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
3. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.

GUTTER & JM DRAIN BAR

DRAWING NO.

E-FE-V7

REPLACES EE-3T

MEMBRANE TYPE:

JM EPDM

MAXIMUM GUARANTEE TERM:

20 YEAR

ISSUE DATE

7-10-17

SCALE

N.T.S

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.

