

Zeston®

300 PVC

Insulated Fitting Covers



SELECTION CHARTS

Zeston 300 PVC insulated fitting covers are sized to fit Micro-Lok® HP and Micro-Lok® HP Ultra fiberglass pipe insulation and all other types of pipe insulation manufactured in accordance with ASTM C585. Note that thickness for rubber and other products vary from fiberglass. Please measure to verify sizing.

Zeston® 300 Series PVC Fitting Covers and Jacketing

For Tees/Valves, 45° Elbows and
Short Radius 90° Elbows

Iron Pipe Size		Pipe Insulation Thickness — in. (mm)							
		½ (13)	1 (25)	1½ (38)	2 (51)	2½ (64)	3 (76)	3½ (89)	4 (102)
½	13	2.0	3.0	4.0	5.0	6.5	7.5	8.5	9.5
¾	19	2.0	3.0	4.0	5.0	6.5	7.5	8.5	9.5
1	25	2.5	3.5	4.5	5.5	6.5	7.5	8.5	9.5
1¼	32	3.0	3.5	5.0	5.5	6.5	7.5	9.5	10.5
1½	38	3.0	4.0	5.0	6.5	7.5	8.5	9.5	10.5
2	51	3.5	4.5	5.5	6.5	7.5	8.5	9.5	10.5
2½	64	4.0	5.0	6.5	7.5	8.5	9.5	10.5	11.5
3	76	4.5	5.5	6.5	7.5	8.5	9.5	10.5	11.5
3½	89	5.0	6.5	7.5	8.5	9.5	10.5	11.5	12.5
4	102	5.5	6.5	7.5	8.5	9.5	10.5	11.5	12.5
4½	114	6.0	7.5	8.5	9.5	10.5	11.5	12.5	14.0
5	127	6.5	7.5	8.5	9.5	10.5	11.5	12.5	14.0
6	152	7.5	8.5	9.5	10.5	11.5	12.5	14.0	15.0
7	178	8.5	9.5	10.5	11.5	12.5	14.0	15.0	16.0
8	203	9.5	10.5	11.5	12.5	14.0	15.0	16.0	17.0
9	229	10.5	11.5	12.5	14.0	15.0	16.0	17.0	18.0
10	254	11.5	12.5	14.0	15.0	16.0	17.0	18.0	19.0
11	279	12.5	14.0	15.0	16.0	17.0	18.0	19.0	20.0
12	305	14.0	15.0	16.0	17.0	18.0	19.0	20.0	21.0
14	356	15.0	16.0	17.0	18.0	19.0	20.0	21.0	22.0
15	381	16.0	17.0	18.0	19.0	20.0	21.0	22.0	23.0
16	406	17.0	18.0	19.0	20.0	21.0	22.0	23.0	24.0
17	432	18.0	19.0	20.0	21.0	22.0	23.0	24.0	25.0
18	457	19.0	20.0	21.0	22.0	23.0	24.0	25.0	26.0
19	483	20.0	21.0	22.0	23.0	24.0	25.0	26.0	27.0
20	508	21.0	22.0	23.0	24.0	25.0	26.0	27.0	28.0

Zeston® 300 Series PVC Fitting Covers and Jacketing

For Tees/Valves, 45° Elbows and
Short Radius 90° Elbows

Copper Tubing Size		Pipe Insulation Thickness — in. (mm)							
		½ (13)	1 (25)	1½ (38)	2 (51)	2½ (64)	3 (76)	3½ (89)	4 (102)
5/8	16	2.0	3.0	3.5	4.5	5.5	6.5	7.5	8.5
7/8	22	2.0	3.0	4.0	5.0	6.0	7.5	8.5	9.5
1 1/8	29	2.0	3.0	4.0	5.0	6.5	7.5	8.5	9.5
1 3/8	35	2.5	3.5	4.5	5.5	6.5	7.5	8.5	9.5
1 5/8	41	2.5	3.5	4.5	5.5	6.5	7.5	8.5	9.5
2 1/8	54	3.0	4.0	5.0	6.0	7.5	8.5	9.5	10.5
2 5/8	67	3.5	4.5	5.5	6.5	7.5	8.5	9.5	10.5
3 1/8	79	4.0	5.0	6.5	7.5	8.5	9.5	10.5	11.5
3 5/8	92	5.0	5.5	6.5	7.5	8.5	9.5	10.5	11.5
4 1/8	105	5.5	6.5	7.5	8.5	9.5	10.5	11.5	12.5
5 1/8	130	6.5	7.5	8.5	9.5	10.5	11.5	12.5	14.0
6 1/8	156	7.5	8.5	9.5	10.5	11.5	12.5	14.0	15.0



Johns Manville

717 17th St.
Denver, CO 80202
800-654-3103
www.JM.com