

Features and Components

Use: JM SP Liquid Flashing Scrim is a polyester based, non-woven reinforcement fabric used in the JM SP Liquid Flashing system. The soft, flexible fabric is designed for use around oddly shaped, difficult penetrations and tying together different roofing substrates.

Type: Polyester fabric, scrim reinforcement layer

Color: White

Features: Improves tear strength and puncture resistance
Easily shaped to fit even the most difficult penetrations
Helps maintain membrane and application uniformity
Available in two widths to fit your flashing requirements



Component

L
Liquid

Type

SC
Scrim
FL
Flashing

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR	APP	SBS					
	HA	CA	HW	HA	CA	HW	SA	MF
<i>Do not use in multi-ply systems</i>								

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
<i>Compatible with all JM single ply systems</i>										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened AD = Adhered BA = Ballasted IW = Induction Welded

Peak Advantage® Guarantee Information

Systems	Guarantee Term
Any JM single ply roofing system.	Up to 20 years*

*Contact JM Technical Services for specific system requirements or guarantee terms.

Tested Physical Properties

Physical Properties		JM SP Liquid Flashing Scrim
Strength	Tensile Strength @ Break	> 1,775 lb
	Elongation, %	> 75%
	Tear Resistance	> 665 lb
	Puncture Strength	> 1,110 lb
Longevity	Physical State	Solid Polyester Fabric
	Nominal Thickness	50 mil
	Weight, g/m ²	165 g/m ²

Installation/Application

- Refer to the JM SP Liquid Flashing Application Guide for full installation and application instructions, including substrate preparation, primer selection, scrim installation, and final resin application.

Packaging and Coverage

Scrim Widths	8.3 in (21 cm)	13.8 in (35 cm)
Scrim Length	164 ft (50 m)	164 ft (50 m)
Rolls per Bag	1 roll	1 roll
Shipping Weight	Approx 4.4 lb (2 kg)	Approx 7.3 lb (3.3 kg)
Scrim Coverage*	113 ft ² (10.5 m ²)	188 ft ² (17.5 m ²)

*Actual scrim coverage will be reduced in areas requiring fleece overlap. Minimum overlap is 2 in (5.1 cm).

Storage

Shelf Life	For best application, product should be used within 5 years of manufacture.
Storage Conditions	Always store inside plastic poly bag in a cool and dry location away from dust and debris. Store rolls flat. Do not let rolls get deformed, creased, or contact water.
Best Practices	Allow product to acclimate at 65 °F - 70 °F (18 °C - 21 °C) for 24 hours prior to use.