


SPECIFICATION NO.

OPTIONAL JM PMMA TEXTURED SURFACING APPLIED OVER JM PMMA MEMBRANE (TEXTURED TRAFFIC COAT OR TEXTURED TOP COAT)

JM PMMA PRIMER APPLIED TO APPROPRIATE SUBSTRATE

JM PMMA MEMBRANE CONSISTING OF JM PMMA RESIN, JM PMMA SCRIM, JM PMMA RESIN



NOTES:

1. REFER TO JOHNS MANVILLE WEBSITE (www.jm.com) FOR MOST UP-TO-DATE INFORMATION.
2. PLEASE SEE JM PMMA FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
3. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
4. JM PMMA MEMBRANE CONSISTS OF JM PMMA RESIN, JM PMMA SCRIM, JM PMMA RESIN. USE THE APPROPRIATE JM PMMA PRIMER DEPENDING ON TYPE OF SUBSTRATE.

DRAWING NO.

LB-MA-02

JM PMMA MEMBRANE ROOF ASSEMBLY

NEW DETAIL

MEMBRANE TYPE:
JM PMMA OVER BITUMINOUS

SCALE
N.T.S

ISSUE DATE
6-18-18

MAXIMUM GUARANTEE TERM:
20 YEAR

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.

