


NOTES:

1. REFER TO JOHNS MANVILLE WEBSITE (www.jm.com) FOR MOST UP-TO-DATE INFORMATION.
2. PLEASE SEE SINGLE PLY FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
3. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL. CONTACT JM TECHNICAL FOR METAL OPTIONS TO BE INCLUDED WITHIN THE JM NDL GUARANTEE.
4. JM TPO EDGE SEALANT IS REQUIRED ON ALL CUT OR NON-ENCAPSULATED EDGES OF REINFORCED MEMBRANE. THIS INCLUDES FACTORY CUT MEMBRANE (SEE DETAIL T-MS-01).

5. SEE DETAIL T-FW-B6 FOR RHINOBOND BASE FLASHING DETAIL. APPROPRIATE SUBSTRATES FOR VERTICAL RHINOBOND APPLICATION INCLUDES PLYWOOD, OSB, METAL STUD WALLS WITH APPROVED SHEATHING.
6. FOR JM APPROVED TOP OF WALL FLASHING METHODS SEE T-FW-T DETAILS.
7. TPO MEMBRANE IS SECURED TO RHINOPLATES USING THE INDUCTION WELDER. SEE THE TPO RHINOPLATE SYSTEM APPLICATION GUIDE FOR FURTHER INFORMATION.
8. TPO RHINOPLATE APPLICATION IS ONLY APPROVED FOR 60 MIL OR THICKER MEMBRANES.

DRAWING NO.		TPO RHINOBOND CONTINUOUS WALL FLASHING ISOMETRIC VIEW		
T-FW-M5I				
NEW DETAIL		MEMBRANE TYPE:	Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.	
SCALE	ISSUE DATE	MEMBRANE TYPE:		
N.T.S	10-12-18	JM TPO	MAXIMUM GUARANTEE TERM:	
			20 YEAR	