



Producto	Uso			Refuerzo		Aplicación		ASTM	Cobertura del rollo*
	Base	Capa	Cubierta superior	Fibra de vidrio	Compuesto	Asfalto caliente 	Fijación mecánica 		
GlasBase® Plus	X	X		X		X	X	D 4601, Tipo II	319 ft ² (29.64 m ²)
GlasKap®			X	X		X		D 3909	101 ft ² (9.38 m ²)
GlasKap® CR G			X	X		X		D 3909	101 ft ² (9.38 m ²)
GlasKap® Plus			X	X		X		D 3909	107 ft ² (9.9 m ²)
GlasPly® IV		X		X		X		D 2178, Tipo IV	531 ft ² (49.33 m ²)
GlasPly® Premier		X		X		X		D 2178, Tipo VI	531 ft ² (49.33 m ²)
GlasTite® Flexible	X	X			X	X	X	D 4601, Tipo II	150 ft ² (13.94 m ²)
PermaPly® 28	X	X		X		X	X	D 4601, Tipo II	300 ft ² (27.87 m ²)
Ventsulation® Felt	X			X			X	D 4897, Tipo II	100 ft ² (9.3 m ²)

*La cobertura del rollo supone un traslape lateral de 2" y un traslape final de 4" para algunos productos. Consulte las hojas de datos del producto.