

**High-Temperature Fiberglass Appliance and Transportation OEM  
Insulation**

Version 3.2

Revision Date 04/22/2021

Print Date 04/22/2021

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Trade name : MICROLITE® MW XG, MICROLITE® WH XG, Range-Glas® XG, SPIN-GLAS® TC XG, SPIN-GLAS® WH XG

**Manufacturer or supplier's details**

Company : Johns Manville  
Address : P.O. Box 5108  
Denver, CO USA 80127

Telephone : +1-303-978-2000  
Emergency telephone number : 24-Hour Number: +1-800-424-9300 (CHEMTREC)

Company : Johns Manville Canada Inc.  
Address : 5301 42 Avenue  
Innisfail, AB Canada T4G 1A2  
Telephone : +1-303-978-2000  
Emergency telephone number : 24-Hour Number: +1-800-424-9300 (CHEMTREC)

**Recommended use of the chemical and restrictions on use**

Restrictions on use : For professional users only.  
Prepared by : productsafety@jm.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Chemical nature**

Glass fiber product

**Hazardous components**

Non-hazardous according to 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015), when used as intended.

**Relevant ingredients**

Chemical name	CAS-No.	Concentration (%)
non-biopersistent (biosoluble) glass fibers	Not Assigned	>= 80 - <= 100 %

## High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.2

Revision Date 04/22/2021

Print Date 04/22/2021

### SECTION 4. FIRST AID MEASURES

General advice	:	Get medical attention if symptoms occur.
If inhaled	:	Move to fresh air. If symptoms persist, call a physician.
In case of skin contact	:	Take off all contaminated clothing immediately. If on skin, rinse well with water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.
In case of eye contact	:	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
If swallowed	:	If symptoms persist, call a physician. Rinse mouth with water to remove dust or fibers and drink plenty of water to help reduce irritation.
Most important symptoms and effects, both acute and delayed	:	Temporary mechanical abrasion (itching) of skin, eyes and respiratory tract may occur upon exposure to fibers or dust during handling of this product and cannot occur unless there is direct contact. Abrasion effects should subside after cessation of exposure.
Protection of first-aiders	:	If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Notes to physician	:	Treat symptomatically.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Carbon dioxide (CO <sub>2</sub> ) Foam Dry powder Water
Unsuitable extinguishing media	:	none
Specific hazards during firefighting	:	Under the influence of high temperatures, e.g. during a fire in the warehouse, decomposition products like carbon oxide may be released due to the low content of organic compounds.
Hazardous combustion products	:	Hydrocarbons carbon oxides nitrogen oxides aldehydes
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Avoid dust formation.
Environmental precautions	:	Should not be released into the environment.

## High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.2

Revision Date 04/22/2021

Print Date 04/22/2021

Methods and materials for containment and cleaning up : Clean up promptly by scoop or vacuum.  
Pick up and arrange disposal without creating dust.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
Minimize dust generation and accumulation.  
Do not breathe vapours/dust.  
Do not get in eyes or mouth or on skin.  
For personal protection see section 8.

Conditions for safe storage : Keep in a dry place.

Materials to avoid : No materials to be especially mentioned.

Further information on storage stability : Stable at normal ambient temperature and pressure.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
synthetic vitreous fibers, glass wool fibers	Not Assigned	TWA	1 fibers/cm <sup>3</sup>	ACGIH
Particulates (insoluble or poorly soluble) Not Otherwise Specified (PNOS)	Not Assigned	TWA (respirable particles)	3 mg/m <sup>3</sup>	ACGIH
		TWA (inhalable particles)	10 mg/m <sup>3</sup>	ACGIH
Inert or Nuisance Dust, Particulates Not Otherwise Regulated (PNOR)	Not Assigned	PEL (Total dust)	15 mg/m <sup>3</sup>	OSHA
		PEL (Respirable fraction)	5 mg/m <sup>3</sup>	OSHA
Fibrous glass dust	Not Assigned	TWA	3 fibers/cm <sup>3</sup>	NIOSH REL
		TWA (total)	5 mg/m <sup>3</sup>	NIOSH REL

As a member of the North American Insulation Manufacturers Association (NAIMA), JM subscribes to the NAIMA Product Stewardship Program (NPSP). Under the NPSP, JM recommends that exposures be limited to the voluntary concentration of 1 f/cc TWA. The NPSP also includes work practice and respiratory protection recommendations. For more information, see NAIMA's Health and Safety Reference Library (website: <http://insulationinstitute.org/tools-resources/resource-library/health-safety/>) to find the Product Stewardship Program Pocket Folder (N052) and other Fact Sheets.

**Engineering measures** : During initial heat-up to operating temperatures above 220 °C (428 °F), thermal decomposition of the organic binder/sizing may occur.  
Use local exhaust ventilation, or other engineering controls to

## High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.2

Revision Date 04/22/2021

Print Date 04/22/2021

maintain airborne levels below exposure limit requirements or guidelines.

If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process.

### Personal protective equipment

- |                             |   |  |
|-----------------------------|---|--|
| Respiratory protection      | : | No personal respiratory protective equipment normally required.<br>During initial heat-up to operating temperatures above 220 °C (428 °F), thermal decomposition of the organic binder/sizing may occur.<br>Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines.<br>If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. |
| Hand protection<br>Material | : | Protective gloves  |
| Remarks                     | : | For prolonged or repeated contact use protective gloves.   |
| Eye protection              | : | Safety glasses with side-shields   |
| Skin and body protection    | : | Wear protective clothing, such as long-sleeved shirts and pants.<br>Change working clothes after each workshift.<br>Remove and wash contaminated clothing before re-use.   |
| Hygiene measures            | : | Handle in accordance with good industrial hygiene and safety practice.   |

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- |   |   |                   |
|---|---|-------------------|
| Appearance                              | : | roll              |
| Colour                                  | : | white             |
| Odour                                   | : | slight            |
| Odour Threshold                         | : | No data available |
| pH                                      | : | Not applicable    |
| Melting point/freezing point            | : | Not applicable    |
| Initial boiling point and boiling range | : | Not applicable    |
| Flash point                             | : | Not applicable    |
| Evaporation rate                        | : | Not applicable    |
| Flammability (solid, gas)               | : | No data available |
| Upper explosion limit                   | : | Not applicable    |
| Lower explosion limit                   | : | Not applicable    |

## High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.2

Revision Date 04/22/2021

Print Date 04/22/2021

Vapour pressure	: Not applicable
Relative vapour density	: Not applicable
Relative density	: No data available
Density	: Not applicable
Solubility(ies)	
Water solubility	: Not applicable
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: Not applicable
Viscosity	
Viscosity, dynamic	: Not applicable
Viscosity, kinematic	: Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored normally.
Conditions to avoid	: None known.
Incompatible materials	: hydrofluoric acid
Hazardous decomposition products	: No hazardous decomposition products are known. During initial heat-up to operating temperatures above 220 °C (428 °F), thermal decomposition of the organic binder/sizing may occur.

### SECTION 11. TOXICOLOGICAL INFORMATION

<b>IARC</b>	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA (29 CFR 1910 Subpart Z, Toxic and Hazardous Substances).
<b>NTP</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Further information

##### Product:

Remarks: During initial heat-up to operating temperatures above 220 °C (428 °F), thermal

## High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.2

Revision Date 04/22/2021

Print Date 04/22/2021

decomposition of the organic binder/sizing may occur. Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process.

Remarks: Temporary mechanical abrasion (itching) of skin, eyes and respiratory tract may occur upon exposure to fibers or dust during handling of this product and cannot occur unless there is direct contact. Abrasion effects should subside after cessation of exposure.

---

### SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : Due to the properties of the product, a hazard to the environment may not be expected.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

Waste from residues : Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

---

### SECTION 14. TRANSPORT INFORMATION

**International transport regulations**

Land transport

USDOT: Not classified as a dangerous good under transport regulations

TDG: Not classified as a dangerous good under transport regulations

Sea transport

IMDG: Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO: Not classified as a dangerous good under transport regulations

## High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.2

Revision Date 04/22/2021

Print Date 04/22/2021

### SECTION 15. REGULATORY INFORMATION

#### TSCA list

TSCA - 5(a) Significant New Use Rule List of Chemicals : Not relevant

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : Not relevant

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

#### California Prop. 65

This product does not require a warning under the California Safe Drinking Water and Toxic Enforcement Act (Proposition 65).

#### The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory

### SECTION 16. OTHER INFORMATION

#### Further information

Revision Date : 04/22/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.