

R-VALUE (hr•sq.ft.°F/BTU)	MINIMUM INSTALLED THICKNESS (in.)	SETTLED THICKNESS (in.)	BAGS PER 1,000 SQ. FT.	MAXIMUM NET COVERAGE (sq.ft./bag)	MINIMUM WEIGHT (lbs./sq.ft.)
To obtain an insulation resistance (R) of:	Installed insulation should not be less than:	Expected thickness after long-term settling has occurred:	Minimum number of bags per 1,000 sq.ft. of net area:	Contents of this bag should not cover more than:	The weight per sq. ft. of installed insulation should not be less than:
10	3.75	3.75	4.1	246.4	0.13
11	4.25	4.25	4.6	215.9	0.15
12	4.50	4.50	4.9	202.8	0.16
13	4.75	4.75	5.2	191.4	0.16
14	5.25	5.25	5.8	171.7	0.18
15	5.50	5.50	6.1	163.3	0.19
16	6.00	6.00	6.7	148.5	0.21
17	6.25	6.25	7.0	142.0	0.22
18	6.75	6.75	7.7	130.5	0.24
19	7.00	7.00	8.0	125.4	0.25
20	7.25	7.25	8.3	120.5	0.26
21	7.75	7.75	8.9	111.9	0.28
22	8.00	8.00	9.3	108.0	0.29
23	8.25	8.25	9.6	104.3	0.30
24	8.75	8.75	10.2	97.6	0.32
25	9.00	9.00	10.6	94.5	0.33
26	9.50	9.50	11.2	88.9	0.35
27	9.75	9.75	11.6	86.3	0.37
28	10.00	10.00	11.9	83.8	0.38
29	10.50	10.50	12.6	79.2	0.40
30	10.75	10.75	13.0	77.1	0.41
31	11.00	11.00	13.3	75.1	0.42
32	11.50	11.50	14.0	71.3	0.44
33	11.75	11.75	14.4	69.5	0.45
34	12.00	12.00	14.7	67.8	0.46
35	12.50	12.50	15.5	64.6	0.49
36	12.75	12.75	15.8	63.1	0.50
37	13.00	13.00	16.2	61.7	0.51
38	13.50	13.50	17.0	59.0	0.53
39	13.75	13.75	17.3	57.7	0.55
40	14.00	14.00	17.7	56.5	0.56
41	14.25	14.25	18.1	55.3	0.57
42	14.75	14.75	18.8	53.1	0.59
43	15.00	15.00	19.2	52.0	0.61
44	15.25	15.25	19.6	50.9	0.62
45	15.75	15.75	20.4	49.0	0.64
46	16.00	16.00	20.8	48.1	0.65
47	16.25	16.25	21.2	47.2	0.67
48	16.50	16.50	21.6	46.3	0.68
49	17.00	17.00	22.4	44.6	0.71
50	17.25	17.25	22.8	43.9	0.72
51	17.50	17.50	23.3	43.1	0.73
52	17.75	17.75	23.6	42.3	0.74
53	18.25	18.25	24.4	40.9	0.77
54	18.50	18.50	24.9	40.2	0.78
55	18.75	18.75	25.3	39.6	0.80
56	19.00	19.00	25.7	38.9	0.81
57	19.25	19.25	26.1	38.3	0.82
58	19.75	19.75	27.0	37.1	0.85

R-VALUE (hr•sq.ft.°F/BTU)	MINIMUM INSTALLED THICKNESS (in.)	SETTLED THICKNESS (in.)	BAGS PER 1,000 SQ. FT.	MAXIMUM NET COVERAGE (sq.ft./bag)	MINIMUM WEIGHT (lbs./sq.ft.)
To obtain an insulation resistance (R) of:	Installed insulation should not be less than:	Expected thickness after long-term settling has occurred:	Minimum number of bags per 1,000 sq.ft. of net area:	Contents of this bag should not cover more than:	The weight per sq. ft. of installed insulation should not be less than:
59	20.00	20.00	27.4	36.5	0.86
60	20.25	20.25	27.9	35.8	0.88
61	20.50	20.50	28.3	35.4	0.89
62	21.00	21.00	29.2	34.3	0.92
63	21.25	21.25	29.6	33.8	0.93
64	21.50	21.50	30.0	33.3	0.95
65	21.75	21.75	30.5	32.8	0.96
66	22.00	22.00	30.9	32.3	0.97
67	22.50	22.50	31.8	31.4	1.00
68	22.75	22.75	32.3	31.0	1.02
69	23.00	23.00	32.7	30.5	1.03
70	23.25	23.25	33.2	30.1	1.05
71	23.50	23.50	33.7	29.7	1.06
72	24.00	24.00	34.6	28.9	1.09
73	24.25	24.25	35.1	28.5	1.10
74	24.50	24.50	35.5	28.1	1.12
75	24.75	24.75	36.0	27.8	1.13
76	25.00	25.00	36.5	27.4	1.15
77	25.25	25.25	37.0	27.1	1.16
78	25.75	25.75	37.9	26.4	1.19
79	26.00	26.00	38.4	26.0	1.21
80	26.25	26.25	38.9	25.7	1.22
81	26.50	26.50	39.4	25.4	1.24
82	26.75	26.75	39.9	25.1	1.26
83	27.00	27.00	40.4	24.8	1.27
84	27.50	27.50	41.3	24.2	1.30
85	27.75	27.75	41.8	23.9	1.32
86	28.00	28.00	42.3	23.6	1.33
87	28.25	28.25	42.8	23.3	1.35
88	28.50	28.50	43.4	23.1	1.37
89	28.75	28.75	43.9	22.8	1.38
90	29.00	29.00	44.4	22.5	1.40
91	29.50	29.50	45.4	22.0	1.43
92	29.75	29.75	45.9	21.8	1.45
93	30.00	30.00	46.4	21.5	1.46
94	30.25	30.25	47.0	21.3	1.48
95	30.50	30.50	47.5	21.1	1.50
96	30.75	30.75	48.0	20.8	1.51
97	31.00	31.00	48.5	20.6	1.53
98	31.50	31.50	49.6	20.2	1.56
99	31.75	31.75	50.1	19.9	1.58
100	32.00	32.00	50.7	19.7	1.60