


SPECIFICATION NO.

PRECAST CONCRETE
PAVERS ON APPROPRIATE
SUPPORT SYSTEM

APPROPRIATE
DRAINAGE LAYER

JM PMMA PRIMER APPLIED
TO CONCRETE SUBSTRATE

JM PMMA MEMBRANE
CONSISTING OF JM PMMA
STANDARD RESIN, JM
PMMA SCRIM, JM PMMA
STANDARD RESIN



NOTES:

1. REFER TO JOHNS MANVILLE WEBSITE (www.jm.com) FOR MOST UP-TO-DATE INFORMATION.
2. PLEASE SEE JM PMMA FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
3. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
4. JM PMMA MEMBRANE CONSISTS OF JM PMMA STANDARD RESIN, JM PMMA SCRIM, JM PMMA STANDARD RESIN. USE THE APPROPRIATE JM PMMA PRIMER DEPENDING ON TYPE OF SUBSTRATE.

DRAWING NO.

LB-MA-03

NEW DETAIL

SCALE

N.T.S

ISSUE DATE

6-18-18

JM PMMA PROTECTED ROOF MEMBRANE ASSEMBLY

MEMBRANE TYPE:

JM PMMA OVER BITUMINOUS

MAXIMUM GUARANTEE TERM:

20 YEAR

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.

