

# Zeston®

## 2000 PVC

Insulated Fitting Covers



## SELECTION CHARTS

Zeston 2000 PVC insulated fitting covers are sized to fit Micro-Lok® HP and Micro-Lok® HP Ultra fiberglass pipe insulation and all other types of pipe insulation manufactured in accordance with ASTM C585. Note that thickness for rubber and other products vary from fiberglass. Please measure to verify sizing.

# IRON PIPE FITTING COVERS

## Insulated Fitting Covers For Tees/Valves, 45° Elbows and Short Radius 90° Elbows

Iron Pipe Size		Pipe Insulation Thickness — in. (mm)									
in.	mm	½ (13)	1 (25)	1½ (38)	2 (51)	2½ (64)	3 (76)	3½ (89)	4 (102)	4½ (114)	5 (127)
¾	10	2	7	9	-	-	-	-	-	-	-
½	13	3	7	10	12	15	17	18	19	20	21
¾	19	4	7	10	12	15	17	18	19	20	21
1	25	5	9	11	13	15	17	18	19	20	21
1¼	32	6	9	12	13	15	17	18	19	20	21
1½	38	7	10	12	15	17	18	19	20	21	22
2	51	9	11	13	15	17	18	19	20	21	22
2½	64	10	12	15	17	18	19	20	21	22	23
3	76	11	13	15	17	18	19	20	21	22	23
3½	89	12	15	17	18	19	20	21	22	23	24
4	102	13	15	17	18	19	20	21	22	23	24
5	127	15	17	18	19	20	21	22	23	24	25
6	152	17	18	19	20	21	22	23	24	25	26
8	203	19	20	21	22	23	24	25	26	27	28
10	254	21	22	23	24	25	26	27	28	29	30†
12	305	23	24	25	26	27	28	29	30†	31†	32†
14	356	24	25	26	27	28	29	30†	31†	32†	33**
16	406	26	27	28	29	30†	31†	32†	33**	-	35**
18	457	28	29	30†	31†	32†	33**	-	35**	-	-
20	508	30†	31†	32†	33**	-	35**	-	-	-	-
22	559	32†	33**	-	35**	-	-	-	-	-	-
24	610	-	35**	-	-	-	-	-	-	-	-

† Only 45° elbows and short radius 90° elbows available for these sizes – no tees/valves.

\*\* Only 45° elbows available for these sizes – no short radius 90° elbows, tees/valves.

# IRON PIPE FITTING COVERS

## Insulated Fitting Covers

For Long Radius 90° Elbows Only

Iron Pipe Size		Pipe Insulation Thickness — in. (mm)									
in.	mm	½ (13)	1 (25)	1½ (38)	2 (51)	2½ (64)	3 (76)	3½ (89)	4 (102)	4½ (114)	5 (127)
¾	10	2	7	9	-	-	-	-	-	-	-
½	13	3	7	10	12	15	17	18	19	20	21
¾	19	4	7	10	12	15	17	18	19	20	21
1	25	5	9	11	13	15	17	18	19	20	21
1¼	32	6	9	12	13	15	17	18	19	20	21
1½	38	7	10	12	15	17	18	19	20	21	22
2	51	9	2x1	13	15	17	18	19	20	21	22
2½	64	10	12	15	17	18	19	20	21	22	23
3	76	3x½	3x1	15 or 3x½	17 or 3x2	18	19	20	21	22	23
3½	89	4x½	15	17	18	19	20	21	22	23	24
4	102	4x½	4x1	17 or 4x1½	18 or 4x2	19	20	21	22	23	24
5	127	5x½	5x1	18 or 5x1½	19 or 5x2	20	21	22	23	24	25
6	152	6x½	6x1	6x1½	20 or 6x2	21	22	23	24	25	26
8	203	8x½	8x1	8x1½	8x2	23	24	25	26	27	28
10	254	10x1	10x1	10x1½	10x2	25	26	27	28	29	30
12	305	12x1	12x1	12x1½	12x2	12x3	12x3	29	30	31	32
14	356	14x1	14x1	14x1½	14x2	14x3	14x3	30	31	32	33
16	406	16x1	16x1	16x1½	16x2	16x3	16x3	32	33	-	35
18	457	18x1	18x1	18x1½	18x2	18x3	18x3	-	35	-	-
20	508	20x1	20x1	20x1½	20x2	20x3	20x3	-	-	-	-
22	559	22x1	22x1	22x1½	22x2	22x3	22x3	-	-	-	-
24	610	24x1	24x1	24x2	24x2	24x3	24x3	-	-	-	-

# COPPER TUBING FITTING COVERS

## Insulated Fitting Covers For Tees/Valves, 45° Elbows and Short Radius 90° Elbows

Copper Tubing Size		Pipe Insulation Thickness — in. (mm)									
in.	mm	½ (13)	1 (25)	1½ (38)	2 (51)	2½ (64)	3 (76)	3½ (89)	4 (102)	4½ (114)	5 (127)
½	13	-	6	9	11	13	15	17	18	19	20
5/8	16	2	7	9	11	13	15	17	18	19	20
7/8	22	3	7	10	12	15	17	18	19	20	21
1 1/8	29	4	8	10	12	15	17	18	19	20	21
1 3/8	35	5	9	11	13	15	17	18	19	20	21
1 5/8	41	6	9	12	13	15	17	18	19	20	21
2 1/8	54	8	10	12	15	17	18	19	20	21	22
2 5/8	67	9	11	13	15	17	18	19	20	21	22
3 1/8	79	10	12	15	17	18	19	20	21	22	23
3 5/8	92	11	13	15	17	18	19	20	21	22	23
4 1/8	105	12	15	17	18	19	20	21	22	23	24
5 1/8	130	15	17	18	19	20	21	22	23	24	25
6 1/8	156	17	18	19	20	21	22	23	24	25	26

## Insulated Fitting Covers For Long Radius 90° Elbows Only

Copper Tubing Size		Pipe Insulation Thickness — in. (mm)									
in.	mm	½ (13)	1 (25)	1½ (38)	2 (51)	2½ (64)	3 (76)	3½ (89)	4 (102)	4½ (114)	5 (127)
½	13	-	6	9	11	13	15	17	18	19	20
5/8	16	2	7	9	11	13	15	17	18	19	20
7/8	22	3	7	10	12	15	17	18	19	20	21
1 1/8	29	-	8	10	12	15	17	18	19	20	21
1 3/8	35	-	9	11	13	15	17	18	19	20	21
1 5/8	41	-	9	11	13	15	17	18	19	20	21
2 1/8	54	-	2x1	12	15	17	18	19	20	21	22
2 5/8	67	-	11	2½x1½	15	17	18	19	20	21	22
3 1/8	79	3x½	3x1	15	17	18	19	20	21	22	23
3 5/8	92	-	4x½	15	17	18	19	20	21	22	23
4 1/8	105	4x½	4x1	17	18	19	20	21	22	23	24
5 1/8	130	15	17	18	19	20	21	22	23	24	25
6 1/8	156	17	18	19	20	21	22	23	24	25	26

# INSULATED FITTING COVERS

## By Cover Size

Use for sizing and ordering factory trimmed MGT fitting covers.

## Victaulic,<sup>†</sup> Gruvlok<sup>‡</sup> Mechanical Groove Type (MGT) Fittings Covers

Iron Pipe Size		Pipe Insulation Thickness — in. (mm)			
in.	mm	½ (13)	1 (25)	1½ (38)	2 (51)
1½	38	✓	✓	✓	-
2*	51*	✓	✓	✓	-
2½	64	✓	✓	✓	-
3*	76*	✓	✓	✓	✓
3½	89	✓	✓	✓	✓
4*	102*	✓	✓	✓	✓
5*	127*	✓	✓	✓	✓
6*	152*	✓	✓	✓	✓
8*	203*	✓	✓	✓	✓
10*	254*	✓	✓	✓	✓
12*	305*	✓	✓	✓	✓
14*	356*	✓	✓	✓	✓
16*	406*	✓	✓	✓	✓
18*	457*	✓	✓	✓	✓

✓ Indicates availability. \* Available in long or short radius. † Victaulic is a registered trademark of Victaulic Company of America. ‡ Gruvlok is a registered trademark of Grinnell Corporation.

All fittings feature wide step-down ends to accommodate multiple insulation thicknesses. The covers are easily field-trimmed to accommodate the required insulation thickness. For iron pipe sizes 2½" and less, insulation thicknesses range from ½" to 1½". For iron pipe sizes 3" up to 18", thickness range from ½" to 2". MGT fittings are made to order. Not for use in applications requiring 2" of insulation over QUICKVIC™ style pipe fittings, or other similar sized mechanical groove type pipe fitting. Contact your service center for a PVC fitting recommendation for this application.

# CUT & CURLED JACKETING

Zeston Fitting Size	OD Size
2–3	2
4–5	2½
6–7	3
8–9	3½
10	4
11	4½
12	5
13	5½
14–15	6–6½
16–17	7–7½
18	8–8½
19	9–9½
20	10–10½
21	11–11½
22	12–12½
23	13–14
24	15
25	16
26	17
27	18
28	19
29	20
30	21
31	22
32	23
33	24
34	25
35	26
36	27
37	28
38	29
39	30

Zeston white and color PVC Cut & Curled Jacketing sizes correspond to Zeston 2000 fitting cover sizes. For example, number 6–7 fits applications requiring number 6 or number 7 fitting covers. If unsure of fitting size or for covering bare pipe, simply measure and order by O.D. size. 30 mil recommended for outdoor applications.

# ZESTON PVC ROLLS

Thickness (mm)	Width (in)	Length (ft)	Area (ft)
10	35½	203	600
15	35½	135	400
20	35½	102	300
20	48	100	400
20	48	50	200
30	35½	102	300
30	35½	67½	200
30	48	100	400
30	48	67½	270
30	48	50	200

# AVAILABLE COLORS



Color PVC is recommended for indoor use only.



**1-800-654-3103**  
**[JM.com/PVCguide](http://JM.com/PVCguide)**



717 17th St.  
Denver, CO 80202  
800-654-3103  
[www.JM.com](http://www.JM.com)