

Bulletin Number: T24-007

Date: June 25, 2025

Distribution: External

Johns Manville Peak Advantage® Guarantee Requirements for JM SECUROCK® Gypsum-Fiber Roof Board in Modified Asphalt and EPDM Systems

In a continuous effort to ensure JM and our approved contractors provide the best possible roof systems to our end customers JM has the following requirements for projects using modified asphalt or EPDM systems that will be requesting a JM Peak Advantage NDL Guarantee:

JM SECUROCK Gypsum-Fiber board thickness must be ½" or greater when installing:

- Adhered modified APP and SBS systems
- Any adhered EPDM system

Specifically for APP and SBS Systems:

- Where the SECUROCK Gypsum-Fiber cover board is fastened, all base, inter, and cap plies must be polyester reinforced.
- Where the SECUROCK Gypsum-Fiber cover board is adhered to either fastened or adhered insulation, all base and inter plies must be polyester reinforced. Cap plies may either be polyester, or fiberglass reinforced.

These requirements do not apply to hybrid TPO or PVC systems, or DynaFast assemblies which include SECUROCK Gypsum-Fiber.

Please visit www.jm.com/roofing to view the latest system requirements and installation guidelines or contact JM Guarantee Services at (800) 922-5922 option 3.

Jeff Caldwell RRO
Florida Regional Services Manager | Roofing Systems