

Features and Components

Use: PermaFlash Scrim is part of the PermaFlash System – an integrated flashing system specially formulated for use in bituminous roofing systems and select single-ply applications. A complete bituminous PermaFlash system also includes PermaFlash Primer when needed and either 1-Part PermaFlash™ or MBR® Flashing Cement and Activator. PermaFlash Scrim may also be used with JM One-Part Pourable Sealer for single-ply flashing applications.

Type: Flexible stitchbonded polyester scrim

Color: White



Component

L
Liquid

Type

SC
Scrim

FL
Flashing

Multi-Ply
Liquid Applied

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF	
Compatible with all multi-ply systems*									

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Compatible with single ply systems										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered
*As part of a complete flashing system

Installation/Application

- For bituminous applications, refer to the application instructions guidelines for proper utilization of this PermaFlash Scrim / MBR® Flashing Cement system.
- For select single-ply applications, refer to the JM One-Part Pourable Sealer Liquid Flashing Installation Guide.

Packaging, Dimensions and Coverage

Roll Size	12 in (305 mm) width x 300 ft (91.4 m) length
Shipping Weight (approx.)	2 lbs (0.9 kg)/roll
Rolls per Box	1 roll per box
Coverage	300 ft² (27.87 m²)
Stocking Locations	Macon, Hazleton, Hillsboro, Lathrop, Scottsboro, Oklahoma City, Rockdale

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.