



JM DRAIN BAR FDB-40 1/4"
(8mm) GAP BETWEEN SECTIONS

JM SINGLE PLY SEALING
MASTIC BEHIND MEMBRANE

APPROPRIATE FASTENERS 6" O.C.

METAL COUNTER
FLASHING BY OTHERS
RE: SMACNA OR NRCA

JM EPDM MEMBRANE
BALLASTED

JM INSULATION / COVER BOARD

WOOD NAILER SECURELY
ANCHORED TO DECK
RE: DETAIL E-FE-M1

APPROVED DECK

NOTES:

1. REFER TO JOHNS MANVILLE WEBSITE (www.jm.com) FOR MOST UP-TO-DATE INFORMATION.
2. PLEASE SEE SINGLE PLY FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
3. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.

ROOF EDGE WITH JM DRAIN BAR

DRAWING NO.
E-FE-V12
FLASHING EDGE

MEMBRANE TYPE:
JM EPDM / JM WHITE EPDM
MAXIMUM GUARANTEE TERM:
20 YEAR

ISSUE DATE
01-30-25
SCALE
N.T.S

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy for general educational purposes only. This complimentary assistance is not to be either used or relied upon by anyone as a substitute for professional engineering design and documentation required by any building code, contract, or applicable law. By accepting the general conceptual information, you agree it does not constitute any representations, endorsements of, or an assumption by Johns Manville of any duty or liability for either the adequacy of the design of a building, any of its components or the sufficiency of any construction.

