

T-JOINT PATCH ALTERNATIVE

- 4. JM EPDM TAPE PRIMER OR JM SINGLE PLY MEMBRANE PRIMER (LOW VOC) MUST BE APPLIED ON ALL MEMBRANE SURFACES COMING INTO CONTACT WITH JM EPDM PEEL & STICK PRODUCTS. ROLL MEMBRANE WITH HAND ROLLER UNDER PRESSURE AT SEAM IN ACCORDANCE WITH THE JM EPDM INSTALLATION GUIDE.
- 5. ROLL PATCH INTO SEAMS WITH HAND ROLLER UNDER PRESSURE AND CREASE INTO SEAMS ACCORDING TO THE JM EPDM APPLICATION GUIDE.
- 6. ALL EDGES WITH EXPOSED JM EPDM SELF ADHERED ADHESIVE MUST BE STRIPPED IN.

## JM EPDM SELF ADHERED MEMBRANE CONTINUOUS BUTTED END LAP

E-MS-19
MEMBRANE SEAMING

DIVIOLLI ADITLIALD MEMBRATA		
	MEMBRANE TYPE:	ISSUE DATE
	JM EPDM SA	11-20-24
	MAXIMUM GUARANTEE TERM:	SCALE
	25 YEAR	N.T.S

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy for general educational purposes only. This complimentary assistance is not to be either used or relied upon by anyone as a substitute for professional engineering design and documentation required by any building code, contract, or applicable law. By accepting the general conceptual information, you agree it does not constitute any representations, endorsements of, or an assumption by Johns Manville of any duty or liability for either the adequacy of the design of a building, any of its components or the sufficiency of any construction.

