









| ASTM | Product | Application | | | | Roll Size | Roll Coverage | Colors* | | | | | | |
|---|--|---|--|--|--|--------------------------------|-----------------------|---------|------|---------|----------|-----------|--------------|--|
| | | Hot Air Weld  | Fully Adhered  | Mechanically Fastened  | Hot Asphalt  | | | White | Grey | Grey ES | Charcoal | Sandstone | Sandstone ES | |
| PVC with Dow Elvaloy KEE Polymer JM PVC with the optimal amount of Dow™ Elvaloy® KEE is a heat weldable polyvinyl chloride thermoplastic membrane that provides superior resistance against oil, fuels, and other hard chemicals. | | | | | | | | | | | | | | |
| D 4434, Type III | 50 MIL | | X | X | | 3.25' x 100' (1 m x 30.48 m) | 325 ft² (30.19 m²) | X | | | | | | |
| | | | X | X | | 5' x 100' (1.52 m x 30.48 m) | 500 ft² (46.45 m²) | | | | | | | |
| | | | X | X | | 6.5' x 100' (1.98 m x 30.48 m) | 650 ft² (60.38 m²) | | | | | | | |
| | | | X | X | | 10' x 100' (3.05 m x 30.48 m) | 1000 ft² (92.9 m²) | | | | | | | |
| | 60 MIL | X | X | X | | 3.25' x 100' (1 m x 30.48 m) | 325 ft² (30.19 m²) | X | X | X | X | X | X | |
| | | X | X | X | | 5' x 100' (1.52 m x 30.48 m) | 500 ft² (46.45 m²) | | | | | | | |
| | | X | X | X | | 6.5' x 100' (1.98 m x 30.48 m) | 650 ft² (60.38 m²) | | | | | | | |
| | | X | X | X | | 10' x 100' (3.05 m x 30.48 m) | 1000 ft² (92.9 m²) | | | | | | | |
| | | X | X | X | | 12' x 100' (3.66 m x 30.48 m) | 1200 ft² (111.5 m²) | | | | | | | |
| | 80 MIL | X | X | X | | 3.25' x 75' (1 m x 22.86 m) | 243.75 ft² (22.65 m²) | X | X | X | X | X | X | |
| | | X | X | X | | 5' x 75' (1.52 m x 22.86 m) | 375 ft² (34.84 m²) | | | | | | | |
| | | X | X | X | | 6.5' x 75' (1.98 m x 22.86 m) | 487.5 ft² (45.29 m²) | | | | | | | |
| | | X | X | X | | 10' x 75' (3.05 m x 22.86 m) | 750 ft² (69.68 m²) | | | | | | | |
| | | X | X | X | | 12' x 75' (3.66 m x 22.86 m) | 900 ft² (83.61 m²) | | | | | | | |
| | PVC mil/MIN with Dow Elvaloy KEE Polymer JM PVC with KEE MIN is a heat weldable thermoplastic membrane with a minimum thickness of either 60 or 72 mils. | | | | | | | | | | | | | |
| D 4434, Type III | 60 MIL MIN | X | X | X | | 3.25' x 100' (1 m x 30.48 m) | 325 ft² (30.19 m²) | X | X | | | | X | |
| | | X | X | X | | 6.5' x 100' (1.98 m x 30.48 m) | 650 ft² (60.38 m²) | | | | | | | |
| | | X | X | X | | 10' x 100' (3.05 m x 30.48 m) | 1000 ft² (92.9 m²) | | | | | | | |
| | 72 MIL MIN | X | X | X | | 6.5' x 75' (1.98 m x 22.86 m) | 487.5 ft² (45.29 m²) | X | | | | | | |

*All colors not available as standard stocked items in all size configurations. Please call for minimums and lead times.

| ASTM | Product | Application | | | | Roll Size | Roll Coverage | Colors* | | | | | |
|---|--|---|--|--|--|--------------------------------|--|---------|------|---------|----------|-----------|--------------|
| | | Hot Air Weld  | Fully Adhered  | Mechanically Fastened  | Hot Asphalt  | | | White | Grey | Grey ES | Charcoal | Sandstone | Sandstone ES |
| PVC FB with Dow Elvaloy KEE Polymer JM PVC with KEE FB is a heat weldable thermoplastic membrane that utilizes a Spunbond 3.8 oz. fleece creating an extremely durable, strong yet light and flexible protection layer. | | | | | | | | | | | | | |
| D 4434, Type III | 60 MIL | X | X | X | X | 6.33' x 90' (1.93 m x 27.43 m) | 569.7 ft ² (52.93 m ²) | X | X | X | X | X | X |
| | | X | X | X | X | 12' x 90' (3.66 m x 27.43 m) | 1080 ft ² (100.34 m ²) | | | | | | |
| | 80 MIL | X | X | X | X | 6.33' x 75' (1.93 m x 22.86 m) | 474.75 ft ² (44.11 m ²) | X | X | X | X | X | X |
| | | X | X | X | X | 12' x 75' (3.66 m x 22.86 m) | 900 ft ² (83.61 m ²) | | | | | | |
| PVC SD Plus JM PVC SD Plus is a heat weldable thermoplastic polyvinyl chloride membrane. | | | | | | | | | | | | | |
| D 4434, Type III | 50 MIL | X | X | X | | 5' x 100' (1.52 m x 30.48 m) | 500 ft ² (46.33 m ²) | X | | | | | |
| | | X | X | X | | 10' x 100' (3.05 m x 30.48 m) | 1000 ft ² (92.96 m ²) | | | | | | |
| | 60 MIL | X | X | X | | 5' x 100' (1.52 m x 30.48 m) | 500 ft ² (46.33 m ²) | X | X | | | | |
| | | X | X | X | | 10' x 100' (3.05 m x 30.48 m) | 1000 ft ² (92.96 m ²) | | | | | | |
| | | X | X | X | | 12' x 100' (3.66 m x 30.48 m) | 1200 ft ² (111.5 m ²) | | | | | | |
| | 60 MIL MIN | X | X | X | | 10' x 100' (3.05 m x 30.48 m) | 1000 ft ² (92.96 m ²) | X | | | | | |
| | 80 MIL | X | X | X | | 5' x 75' (1.52 m x 22.9 m) | 375 ft ² (34.84 m ²) | X | X | | | | |
| | | X | X | X | | 10' x 75' (3.05 m x 22.9 m) | 750 ft ² (69.67 m ²) | | | | | | |
| | | X | X | X | | 12' x 75' (3.66 m x 22.86 m) | 900 ft ² (83.61 m ²) | | | | | | |
| | PVC SD Plus FB JM PVC SD Plus is a heat weldable thermoplastic membrane that utilizes a Spunbond 3.8 oz. fleece creating an extremely durable, strong yet light and flexible protection layer. | | | | | | | | | | | | |
| D 4434, Type III | 60 MIL | X | X | X | X | 6.33' x 90' (1.93 m x 27.43 m) | 569.7 ft ² (52.93 m ²) | X | X | | | | |
| | | X | X | X | X | 12' x 90' (3.66 m x 27.43 m) | 1080 ft ² (100.34 m ²) | | | | | | |
| | 80 MIL | X | X | X | X | 6.33' x 75' (1.93 m x 22.86 m) | 474.75 ft ² (44.11 m ²) | X | X | | | | |
| | | X | X | X | X | 12' x 75' (3.66 m x 22.86 m) | 900 ft ² (83.61 m ²) | | | | | | |

*All colors not available as standard stocked items in all size configurations. Please call for minimums and lead times.